



Air-Cooled Condenser
with Microchannel Coil Technology
Models NRG | NRJ



Table of Contents

| | |
|----------------------------------|----|
| Nomenclature | 2 |
| Features & Benefits..... | 3 |
| Capacity and Specifications..... | 4 |
| Energy Performance | 5 |
| Sound Performance..... | 6 |
| Condenser Selection | 7 |
| Dimensional Data..... | 8 |
| Typical Wiring Diagrams..... | 10 |



Nomenclature

| NR | G | D | 02 | A | 014 |
|--|----------------------------------|----------|--------------------------------------|----------------------|-------------------------|
| Product Line | Motor Identifier | Width | # of Fans | Model Identifier | Standard Capacity |
| NR = Air-cooled Condenser with Microchannel Coil | G = 710 mm VSEC J = 710 mm AC | D = Dual | 02 = 2 04 = 4 06 = 6 08 = 8 | A = Current Revision | (MBH/Degree TD, R-404A) |

Features & Benefits

Standard Features

- Microchannel heat exchanger
- R-404A, R-407A/F, R-407C, R-448A, R-449A, R-507, R-422D, and R-410A compatible
- 208-230/3/60 or 460/3/60
- Factory installed manifolding (Single circuit standard)
- 20" clearance legs
- Copper connection points with Schrader access valves
- NRG units are factory wired for customer supplied analog signal
- NRG units are direct acting, series wired motor control
- Through-the-door non-fused disconnect switch
- End access panels for coil-cleaning
- Internal baffles between all fan cells
- NRJ units come standard with individual motor fusing

Optional Features

All Models

- 40" clearance legs
- Export crating

NRG Models

- Individual motor circuit breakers
- Individual motor fusing
- Factory installed analog board (CPC, Danfoss or Novar)
- Motor control & wiring
 - Direct acting (parallel wired)
 - Reverse acting (series or parallel wired)
- Proportional pressure control

NRJ Models

- Ambient fan cycling (electronic)
- Pressure fan cycling (mechanical or electronic)
- Microprocessor relay board (CPC, Danfoss or Novar)
- Control circuit transformer (230/115/24)

Key Benefits

Refrigerant Charge Reduction

Microchannel coils offer a very high primary to secondary surface area ratio. This provides very efficient heat exchange while maintaining a low internal tube volume. As a result, the microchannel condenser reduces condenser refrigerant charge by over 70% (NRGD02A014 vs. BNED02A015).

Energy Efficient

The microchannel air-cooled condensers are available with variable speed EC motors, which vary speed based on system requirements to provide optimal energy and sound performance. These condensers are also available with VFD compatible AC motors.

Corrosion Resistance

The mono-metal construction of the microchannel coils virtually eliminates the risk of galvanic corrosion. A zinc cladding standard on all coils provides additional corrosion resistance for harsh environments.

Sound

Microchannel air-cooled condensers feature quiet variable speed EC fan motors as a standard. Optional VFD compatible AC fan motors are also available.

Lighter Weight

Over 20% lighter than comparable round-tube, plate fin air-cooled condensers.

Lower Height

Approximately 25% lower cabinet height (with same clearance) than comparable round-tube, plate fin condensers.

Structural Robustness

The coils used in this unit are extremely rigid and resistant to damage.

Warranty

Microchannel air-cooled condensers feature a standard 2 year product warranty and a 7 year warranty on the microchannel coil. The VFD compatible AC motors have a 2 year warranty while the variable speed EC motors come with a 3 year warranty.

Environmentally Friendly

100% recyclable, all -aluminum coil.

Condenser Capacities & Specifications

| Model | Air Mover | Capacity (MBH/1°F) | | | | | Full Speed Airflow (ft ³ /min) | Flooded Refrigerant Charge (lbs) | | | Net Wt. (lbs) | Ship Wt. (lbs) | Coil Connection Sizes | |
|------------|-------------|--------------------|---------|--------------|---------|---------|---|----------------------------------|------------------|-------------|---------------|----------------|-----------------------|--------------|
| | | R-404A | R-407C* | R-407A/407F* | R-448A* | R-449A* | | R-404A | R-407C/448A/449A | R-407A/407F | | | Inlet (in.) | Outlet (in.) |
| NRGD02A014 | 710 mm VSEC | 13.5 | 12.7 | 13.2 | 13.0 | 13.4 | 13,700 | 10 | 10 | 11 | 510 | 640 | (1) 1-1/8 | (1) 7/8 |
| NRGD04A027 | 710 mm VSEC | 27.0 | 25.4 | 26.5 | 25.9 | 26.7 | 27,400 | 20 | 21 | 21 | 1015 | 1230 | (2) 1-1/8 | (2) 7/8 |
| NRGD06A041 | 710 mm VSEC | 40.5 | 38.1 | 39.7 | 38.9 | 40.1 | 41,100 | 30 | 31 | 32 | 1520 | 1810 | (3) 1-1/8 | (3) 7/8 |
| NRGD08A054 | 710 mm VSEC | 54.0 | 50.8 | 52.9 | 51.8 | 53.5 | 54,800 | 40 | 42 | 42 | 2005 | 2360 | (4) 1-1/8 | (4) 7/8 |
| NRJD02A014 | 710 mm AC | 13.5 | 12.7 | 13.2 | 13.0 | 13.4 | 13,700 | 10 | 10 | 11 | 510 | 640 | (1) 1-1/8 | (1) 7/8 |
| NRJD04A027 | 710 mm AC | 27.0 | 25.4 | 26.5 | 25.9 | 26.7 | 27,400 | 20 | 21 | 21 | 1015 | 1230 | (2) 1-1/8 | (2) 7/8 |
| NRJD06A041 | 710 mm AC | 40.5 | 38.1 | 39.7 | 38.9 | 40.1 | 41,400 | 30 | 31 | 32 | 1520 | 1810 | (3) 1-1/8 | (3) 7/8 |
| NRJD08A054 | 710 mm AC | 54.0 | 50.8 | 52.9 | 51.8 | 53.5 | 54,800 | 40 | 42 | 42 | 2005 | 2360 | (4) 1-1/8 | (4) 7/8 |

*Based on midpoint condensing temperature

† Does not include manifolding

Condenser Manifolding Specifications for Single Circuit

| Model | Connection Sizes | |
|------------|------------------|--------------|
| | Inlet (in.) | Outlet (in.) |
| NR*D02A014 | (1) 1-1/8 | (1) 7/8 |
| NR*D04A027 | (1) 2-1/8 | (1) 1-5/8 |
| NR*D06A041 | (1) 2-1/8 | (1) 1-5/8 |
| NR*D08A054 | (1) 2-5/8 | (1) 2-1/8 |

* = G for VSEC, J for AC

Contact factory for connection size if not single circuit

Circuiting Options

| Model | Connection Sizes |
|------------|--|
| NR*D02A014 | Only single circuit available |
| NR*D04A027 | Single circuit and 50/50 split available |
| NR*D06A041 | Single circuit, 33/33/33 and 66/33 split available |
| NR*D08A054 | Single Circuit, 50/50 split and 75/25 split available, also 25/25/25/25 and 50/25/25 |

* = G for VSEC, J for AC

Condenser Electrical Specifications


| Model | 208-230/3/60 | | | 460/3/60 | | |
|------------|--------------|------|------|----------|------|------|
| | FLA | MCA | MOPD | FLA | MCA | MOPD |
| NRGD02A014 | 4.0 | 15.0 | 15 | 2.0 | 15.0 | 15 |
| NRGD04A027 | 8.0 | 15.0 | 15 | 4.0 | 15.0 | 15 |
| NRGD06A041 | 12.0 | 15.0 | 15 | 6.0 | 15.0 | 15 |
| NRGD08A054 | 16.0 | 20.0 | 20 | 8.0 | 15.0 | 15 |
| NRJD02A014 | 9.6 | 15.0 | 20 | 5.6 | 15.0 | 15 |
| NRJD04A027 | 19.2 | 20.4 | 30 | 11.2 | 15.0 | 15 |
| NRJD06A041 | 28.8 | 30.0 | 40 | 16.8 | 20.0 | 25 |
| NRJD08A054 | 38.4 | 39.6 | 50 | 22.4 | 23.1 | 30 |

Note: These units are optimized for operation at, or below, 15°F TD. Operation above 15°F TD may result in excessive pressure drop.

Condenser Performance: Energy Consumption

| Model | Energy Consumption (kW) | | | |
|------------|-------------------------|--------------|--------------|---------------|
| | At 30% Speed | At 50% Speed | At 70% Speed | At 100% Speed |
| NRGD02A014 | 0.1 | 0.3 | 0.6 | 1.6 |
| NRGD04A027 | 0.2 | 0.5 | 1.2 | 3.2 |
| NRGD06A041 | 0.3 | 0.8 | 1.8 | 4.9 |
| NRGD08A054 | 0.3 | 1.0 | 2.4 | 6.5 |
| NRJD02A014 | 0.3 | 0.5 | 1.0 | 2.4 |
| NRJD04A027 | 0.6 | 1.0 | 2.0 | 4.8 |
| NRJD06A041 | 0.8 | 1.5 | 3.0 | 7.2 |
| NRJD08A054 | 1.1 | 2.0 | 4.0 | 9.6 |

Power Consumption Performance



NRJ shown with use of a VFD


SOUND PERFORMANCE

Condenser Performance: Sound Pressure

| Model | Sound Pressure (dBA @ 10 ft) | | | |
|------------|------------------------------|--------------|--------------|---------------|
| | At 30% Speed | At 50% Speed | At 70% Speed | At 100% Speed |
| NR*D02A014 | 44.3 | 50.6 | 57.6 | 66.5 |
| NR*D04A027 | 47.3 | 53.7 | 60.6 | 69.5 |
| NR*D06A041 | 49.1 | 55.4 | 62.4 | 71.3 |
| NR*D08A054 | 50.3 | 56.7 | 63.6 | 72.5 |

* = G for VSEC, J for AC

Sound Comparison Chart



Source: <http://www.sengpielaudio.com/tableofsoundpressurelevels.htm> > Adjusted to 10ft

CONDENSER SELECTION

Capacity for air-cooled condensers are based on Total Heat of Rejection (THR) at the condenser. Total heat of rejection is equal to net refrigeration at the evaporator (compressor capacity) plus the energy input into the refrigerant by the compressor (heat of compression). The heat of compression will vary depending on the compressor manufacturer, type of compressor and the operating conditions of the compressor. Whenever possible, it is recommended that you obtain the heat of compression value from the compressor manufacturer.

If this is not available, the THR can be estimated using the following formula:

$$\text{THR} = (\text{Compressor Capacity}) * (\text{Heat of Compression Factor, Tables 1 \& 2})$$

Table 1 contains heat of compression factors for suction cooled compressors and Table 2 contains factors for open drive compressors. For refrigeration systems beyond the range of Tables 1 and 2, use the following equations to estimate THR:

Open Compressors:

$$\text{THR} = \text{Compressor Capacity (BTUH)} + (2545) * (\text{Break Horsepower, BHP})$$

Suction Cooled Compressors:

$$\text{THR} = \text{Compressor Capacity (BTUH)} + (3413 * \text{KW})$$

The compressor capacity is affected by its altitude. If the condenser location is above sea level, an additional correction is required to the THR, as follows:

$$\text{THR (altitude)} = \text{THR} * \text{Altitude Correction Factor, Table 3}$$

Selection Example

| | |
|-------------------------|-------------------------------|
| Compressor capacity: | 270,000 BTUH |
| Evaporator temperature: | +25° F |
| Condensing temperature: | 110° F |
| Ambient temperature: | 95° F |
| Refrigerant: | R-404A |
| Compressor type: | Semi-hermetic, suction cooled |
| Condenser type: | NRG |
| Condenser altitude: | 1,000 feet |

Step 1: Estimate Condenser THR

From Table 1 for suction cooled compressors, at +25° F suction and 115° F condensing temperature, select a heat of compressor factor of 1.335.

$$\begin{aligned} \text{THR} &= \text{Compressor Capacity} * \text{Heat of Compression Factor} \\ &= 270,000 * 1.335 \\ &= 360,450 \end{aligned}$$

Step 2: Correct for Altitude

From Table 3 obtain an altitude correction factor of 1.02 for 1,000 feet.

$$\begin{aligned} \text{THR} &= \text{THR (from step 1)} * \text{Altitude Correction Factor (design)} \\ &= 360,450 * 1.02 \\ &= 367,659 \end{aligned}$$

Step 3: Calculate Design Condenser T.D.

$$\begin{aligned} \text{Design Condenser T.D.} &= \text{Condensing Temp} - \text{Ambient Temp} \\ &= 110^{\circ}\text{F} - 95 \\ &= 15^{\circ}\text{T.D.} \end{aligned}$$

Step 4: Condenser Selection

Condenser capacities are located on page 4. These capacities are given in MBH/°TD. Convert the THR calculated in step 2 to MBH/°TD by dividing by 1,000 to get THR in MBH. Then divide the THR by the design TD to get MBH/°TD.

$$\text{THR (MBH)} = 367,659 / 1,000 = 367.7$$

$$\text{THR (MBH/°TD)} = 367.7 / 15 = 24.5$$

Locate the capacity column and read down until you locate a value equal to or just larger than 24.5. This value is 27.0. Read horizontally to the left to obtain a condenser model of NRGD04A027

Step 5: Calculate Actual T.D. and Condensing Temperature

The actual condenser T.D. can be calculated by dividing the design THR by the condenser rating.

$$\text{Actual T.D.} = \text{THR (Design)} / (\text{Rating @ } 1^{\circ}\text{T.D.})$$

$$= 367.7 / 27.0$$

$$= 13.6^{\circ}\text{F T.D.}$$

The actual condensing temperature is the actual T.D. plus the ambient temperature.

$$\text{Actual Condensing Temperature} = (\text{Actual T.D.}) + (\text{Ambient})$$

$$= 13.6 + 95$$

$$= 108.6^{\circ}\text{F.}$$

*Correction factors based on midpoint condensing temperature.

Table 1. Heat of Compression Factor for Suction Cooled Compressors

| Suction Temp. °F | Condensing Temperature °F | | | | |
|------------------|---------------------------|------|------|------|------|
| | 90° | 100° | 110° | 120° | 130° |
| -40° | 1.56 | 1.63 | 1.72 | 1.81 | 1.94 |
| -30° | 1.49 | 1.55 | 1.62 | 1.70 | 1.80 |
| -20° | 1.43 | 1.49 | 1.55 | 1.62 | 1.70 |
| -10° | 1.38 | 1.43 | 1.49 | 1.55 | 1.63 |
| 0° | 1.34 | 1.38 | 1.43 | 1.49 | 1.56 |
| 5° | 1.31 | 1.36 | 1.41 | 1.48 | 1.55 |
| 10° | 1.29 | 1.34 | 1.39 | 1.44 | 1.52 |
| 15° | 1.26 | 1.31 | 1.36 | 1.41 | 1.48 |
| 20° | 1.24 | 1.28 | 1.33 | 1.38 | 1.44 |
| 25° | 1.22 | 1.26 | 1.31 | 1.36 | 1.42 |
| 30° | 1.20 | 1.24 | 1.28 | 1.33 | 1.39 |
| 40° | 1.17 | 1.20 | 1.24 | 1.28 | 1.33 |
| 50° | 1.13 | 1.16 | 1.20 | 1.24 | 1.28 |

Table 2. Heat of Compression Factor for Open Drive Compressors

| Evap. Temp. °F | Condensing Temperature °F | | | | | |
|----------------|---------------------------|------|------|------|------|------|
| | 90° | 100° | 110° | 120° | 130° | 140° |
| -30° | 1.37 | 1.42 | 1.47 | — | — | — |
| -20° | 1.33 | 1.37 | 1.42 | 1.47 | — | — |
| -10° | 1.28 | 1.32 | 1.37 | 1.42 | 1.47 | — |
| 0° | 1.24 | 1.28 | 1.32 | 1.37 | 1.41 | 1.47 |
| 5° | 1.23 | 1.26 | 1.30 | 1.35 | 1.39 | 1.45 |
| 10° | 1.21 | 1.24 | 1.28 | 1.32 | 1.36 | 1.42 |
| 15° | 1.19 | 1.22 | 1.26 | 1.30 | 1.34 | 1.40 |
| 20° | 1.17 | 1.20 | 1.24 | 1.28 | 1.32 | 1.37 |
| 25° | 1.16 | 1.19 | 1.22 | 1.26 | 1.30 | 1.35 |
| 30° | 1.14 | 1.17 | 1.20 | 1.24 | 1.27 | 1.32 |
| 40° | 1.12 | 1.15 | 1.17 | 1.20 | 1.23 | 1.28 |
| 50° | 1.09 | 1.12 | 1.14 | 1.17 | 1.20 | 1.24 |


Table 3. Altitude Correction Factors

| Altitude | Correction Factor | Altitude | Correction Factor |
|----------|-------------------|----------|-------------------|
| 0 | 1.00 | 4,000 | 1.10 |
| 1,000 | 1.02 | 5,000 | 1.12 |
| 2,000 | 1.05 | 6,000 | 1.15 |
| 3,000 | 1.07 | 7,000 | 1.17 |

Table 4. Capacity & Refrigerant Charge Correction Factors


| Correction Factor | Capacity | Refrigerant Charge |
|------------------------|----------|--------------------|
| R-404A | 1.00 | 1.00 |
| R-407A | 0.98* | 1.04 |
| R-407C | 0.94* | 1.05 |
| R-407F | 0.98* | 1.07 |
| R-448A | 0.96* | 1.05 |
| R-449A | 0.99* | 1.05 |
| R-22 | 1.02 | 1.09 |
| R-410A | 1.02 | 1.07 |
| R-507 | 1.00 | 1.00 |
| NRG 50 Hz Power Supply | 1.00 | - |
| NRJ 50 Hz Power Supply | 0.92 | - |

Front View




Side View


2 Fan




4 Fan



6 Fan




8 Fan




Top View


2 Fan




4 Fan



6 Fan




8 Fan




TYPICAL WIRING DIAGRAM

Diagram 1



TYPICAL WIRING DIAGRAM

Diagram 2





2175 West Park Place Blvd. · Stone Mountain, GA 30087
Phone: 800.537.7775 · Fax: 770.465.5900
heatcrafrpd.com

CLIMATE

CONTROL

Since product improvement is a continuing effort, we reserve the right to make changes in specifications without notice.

CC-ACCMX | Version 001